

## Product Description

The single-mode patch cord is a section of fiber optic cable with a length of 3 or 5 meters, terminated on both ends with SC/APC connectors.

- **Model :** TR-LC/PC
- **Connectors :** LC/PC – LC/PC
- **Length :** 3,5 mtr ( Any Customize length available )
- **Channels :** : Simplex
- **Precision :** : Single mode



## Specification

|                              |  |
|------------------------------|--|
| <b>CONNECTOR TYPE</b>        | <ul style="list-style-type: none"> <li>• LC</li> </ul>   |
| <b>OPTICAL FIBER</b>         | <ul style="list-style-type: none"> <li>• Single- Mode</li> </ul>   |
| <b>CABLE TYPE</b>            | <ul style="list-style-type: none"> <li>• LSZH</li> <li>• 3.0mm / 2.0mm</li> </ul>  |
| <b>CABLE COLOR</b>           |  |
| <b>LENGTH</b>                | <ul style="list-style-type: none"> <li>• 3m,5m Other Length on request</li> </ul>  |
| <b>WORKING TEMPRATURE</b>    | <ul style="list-style-type: none"> <li>• -10°C- +70 °C</li> </ul>  |
| <b>STORAGE TEMPRATURE</b>    | <ul style="list-style-type: none"> <li>• -20°C- +70 °C</li> </ul>  |
| <b>OPTICAL SPECIFICATION</b> |  |
| <b>Insertion Loss</b>        | <ul style="list-style-type: none"> <li>• <b>Typical:</b> 0.2dBm Max.</li> <li>• <b>0.3dB MTRJ:</b> Max. 0.5dB</li> </ul> |

**Return Loss**

- PC: 45dB, UPC 50 dB, APC 60dB

**MECHANICAL SPECIFICATION****Connector Ferrule**

Ceramic

**Repeatability**

0.2dB 200 times mating cycles