

TRICOM MEDIA CONVERTER CHASSIS RACK

Product Description

Rack-mounted chassis is a centralized and economical equipment of gather Ethernet media converter together. It is mostly used in plant room with centralized dual power supply and automatic switch. Normal size is 2U, 14 slots kind is for standalone device.

Features

- * Main and vice power equipment ensure system work smoothly.
- * Function cards supports hot-plugging and each card realizes its corresponding function independently.
- * Double power panel slot supports two power supply units backup for each other.
- * It would enhance the reliability of the rack.
- * Supports 220V/110V AC switch mode power supply (SMPS) design.
- * Power supply and other parameter state indicator LED can monitor the operation condition of system.
- * With stable performance, large capacity of power supply, and easy for management and maintenance.
- * All of the modules installed in the chassis are hot-swap, which makes it unnecessary to power-down the chassis when replacing modules.
- * Support telecommunication operation requirement completely.

Technology Specification

Structure	2U Rack
Ripple wave	20mv
Power input	AC85~265V 50/60HZ
Power output	DC5V 16A
Power adapter	single power supply or dual power supply
Power	95W
Operating Temperature	-10~55°C
Operating Humidity	5%~95%
Storage Temperature	-40~70°C
Storage Humidity	5%~95% no condensing
Dimension	490mm x 230mm x 90mm for Rack

